

# FIBROPROTEX TIPO D



AUXILIARY IMPREGNATING AGENT FOR  
ASBESTOS-CEMENT SLABS

---

## DESCRIPTION

Acetovinyl copolymer water base of red color.

The product dries by evaporation of water, leading to the formation of a red film.

## USE

To be applied to avoid the dispersion of fibers in the environment to support removal interventions (Article 5, paragraph 5 of Ministerial Decree 6 September 1995) and during the disposal of materials containing asbestos.

## APPLICATION

1. Type D encapsulating coatings

On asbestos-cement slabs a low pressure spraying must be carried out, depositing the product on the entire visible surface, for a consumption of about 0.30 l/m<sup>2</sup>.

The thickness of the dry film is 20-25 microns, considering a support absorption of 0.20 lt.

The same treatment must be repeated after the removal of the plates, consolidating all exposed surfaces.

2. Other manufactured goods

Apply the product by spraying at low pressure on all surfaces until the decoesionate parts are completely saturated.

## TECHNICAL SPECIFICATIONS

| PRODUCT DATA                                  |  |
|---|--|
| Colour  | Red  |
| Specific gravity (at 25 °C):<br>mixture (A+B) | 1,00 - 1,05 g/ml   |
| Viscosity (at 25 °C):<br>mixture (A+B)        | 10-20 mPascal (spindle 1, rpm 200)                                     |
| Dry residue (A+B)                             | 25% by weight  |
| Flash point                                   | None   |
| Solvent for cleaning tools                    | Water  |
| Hazard symbols on labels                      | none   |
| Storage                                       | 12 months store in a dry place at a temperature between 5 °C and 35 °C |
| APPLICATION DATA AND TIMES                    |  |
| Dry to the touch (50% R.H.)                   | at 5 °C 40-45 min<br>at 25 °C 25-35 min<br>at 35 °C 10-20 min          |

| Environmental conditions of use | Temperatures between +5 °C and +28 °C and R.H. < 80% |
|---------------------------------|--|
| PERFORMANCE TECHNICAL DATA      |  |
| Appearance                      | Liquid   |

*Product for professional use, the buyer undertakes to follow the above warnings in the application of the purchased product and the instructions in the safety data sheet.*