

POLYURETHANE WATER TOP-COATINGS

COLORSIVIT VISTA

Waterborne polyurethane coating

Ready-to-use one-component gel for decorative skim coat. Particularly suitable for highlighting matheric effects on both floors and walls.

Description

Ready-to-use one-component product based on polyurethane dispersion. It originates a continuous film with excellent mechanical properties that allows to confer particular aesthetic effects on matheric systems.

Use

Decorative cycles in interior, for floor or wall.

Application

As an intermediate in spatulate systems before applying finishes:

- apply with an American trowel or plastic trowel with consumption of 0.10-0.15 kg/m²

As colored glaze in spatulate cycles before applying finishes:

- pigment the product with 0.5% of COLORPASTA W and mix with a mechanical agitator
- apply with an American trowel or plastic spatula with consumption of 0.10-0.15 kg/m²

Avoid product excesses that could cause delays in the development of film characteristics or increased sensitivity to water.

Technical specifications

PRODUCT DATA	
Colour	Transparent
Consumption	0,10-0,15 kg/m ²
Specific gravity (at 25°C)	1,00 +/- 1,05 g/ml
Viscosity (at 25°C)	10.000 +/- 2.000 mPa*s
Solid Content	40% in peso
Flash point	None
Solvent for cleaning tools	Water (before film formation) and Ethyl alcohol (after)
Storage	12 months, store in a dry place at a temperature between 5 °C and 35 °C

APPLICATION DATA AND TIMING	
Recommended thinner	Water
Tack free (50% R.H.)	at 10°C 40-60 min at 25°C 20-30 min at 30°C 5-15 min
Overcoating (50% R.H.)	at 25°C 90 min

Product for professional use. The purchaser undertakes to strictly follow the above warnings when applying the purchased product and the instructions in the safety data sheet.

COLORSIVIT VISTA • Technical sheet • 05/11/2025

Sivit S.r.l.

Via Centallo 57, 10156, Torino, Italia | P.I. - C.F. 01012820013 | C.C.I.A.A. N. 478878 | Reg. Soc. Tribunale Torino N. 305/74
Sistema di gestione conforme alle ISO 9001:2015 – ISO 14001:2015 – ISO 45001:2018
commerciale@sivit.it | sivitsrl@pec.it | +39 011 273 00 33 | www.sivit.it

APPLICATION DATA AND TIMING

Ambiental conditions of application

Temperatures between +10°C and +30°C and R.H. < 70%

Product for professional use. The purchaser undertakes to strictly follow the above warnings when applying the purchased product and the instructions in the safety data sheet.

COLORSIVIT VISTA • Technical sheet • 05/11/2025

Sivit S.r.l.

Via Centallo 57, 10156, Torino, Italia | P.I. - C.F. 01012820013 | C.C.I.A.A. N. 478878 | Reg. Soc. Tribunale Torino N. 305/74

Sistema di gestione conforme alle ISO 9001:2015 – ISO 14001:2015 – ISO 45001:2018

commerciale@sivit.it | sivit srl@pec.it | +39 011 273 00 33 | www.sivit.it