

FUNDS, CONSOLIDANTS, PRIMERS

FONDO PER PIASTRELLE A+B

Water-based two-component basecoat. Primer particularly suitable as adhesion promoter on tiles and ceramic surfaces. It works also on other several materials.



Description

Two-component water-based epoxy system that after cross linking has good adhesion on different substrates (tiles, concrete and old resins).

Compared to water-based epoxy systems available on the market, it has a faster touch out-of-touch.

Use

Tile primer.

Primer for concrete supports and old resin coatings.

Preparation of the support

Surface abrasivation and dedusting.

In the case of newly built concrete, wait 28 days.

N.B.: proper surface preparation is essential to ensure the durability of floor products.

Application

Pour component "A" into component "B" and mix carefully for at least 2 minutes until a homogeneous mixture is obtained.

Apply the product using a roller or brush.

The product consumption is about 0.13 kg/m²

Technical specifications

PRODUCT DATA	
Colour	White
Specific gravity (at 25 °C)	mixture (A+B): 1,30 +/- 0,05 g/ml
Viscosity (at 25 °C)	mixture (A+B): 600 +/- 160 mPa*s
Dry residue (A+B)	62% by weight and 50.6% by volume
VOC ready to use (Legislative Decree 161/06)	<50g/l
Solvent for cleaning tools	Water
Storage	12 months store in a dry place at a temperature between 15 °C and 35 °C

APPLICATION DATA AND TIMES	
Mixture ratio	by weight: A=100, B=56 by volume: A=100, B=195
Pot-life (50% R.H.)	at 10°C 3.5 hours at 25°C 2 hours at 35°C 1.5 hours
Dry to the touch (50% R.H.)	at 10°C 8-10 hours at 25°C 2 hours at 35°C 1.5hours
Coverage (50% R.H.)	at 23°C 12 to 36 hours

Product for professional use. The purchaser undertakes to strictly follow the above warnings when applying the purchased product and the instructions in the safety data sheet.

APPLICATION DATA AND TIMES

Environmental conditions of use	Temperatures between +15 °C and +30 °C and R.H. < 70% Minimum operating temperature: 5 °C
---------------------------------	---

PERFORMANCE TECHNICAL DATA

Appearance	Satin
------------	-------

Product for professional use. The purchaser undertakes to strictly follow the above warnings when applying the purchased product and the instructions in the safety data sheet.

