

FUNDS, CONSOLIDANTS, PRIMERS

FONDO PER PIASTRELLE A+B

Water-based two-component basecoat. Primer particularly suitable as adhesion promoter on tiles and ceramic surfaces. It works also on other several materials.

CE

Description

Two-component water-based epoxy system that after cross linking has good adhesion on different substrates (tiles, concrete and old resins).

Compared to water-based epoxy systems available on the market, it has a faster touch out-of-touch.

Use

Tile primer.

Primer for concrete supports and old resin coatings.

Preparation of the support

Surface abrasivation and dedusting.

In the case of newly built concrete, wait 28 days.

N.B.: proper surface preparation is essential to ensure the durability of floor products.

Application

Pour component "A" into component "B" and mix carefully for at least 2 minutes until a homogeneous mixture is obtained.

Apply the product using a roller or brush.

The product consumption is about 0.13 kg/m²

Technical specifications

PRODUCT DATA	
Colour	White
Specific gravity (at 25 °C)	mixture (A+B): 1,30 +/- 0,05 g/ml
Viscosity (at 25 °C)	mixture (A+B): 600 +/- 160 mPa•s
Dry residue (A+B)	62% by weight and 50.6% by volume
VOC ready to use (Legislative Decree 161/06)	<50g/l
Solvent for cleaning tools	Water
Storage	12 months store in a dry place at a temperature between 15 °C and 35 °C

APPLICATION DATA AND TIMES	
Mixture ratio	by weight: A=100, B=56 by volume: A=100, B=195
Pot-life (50% R.H.)	at 10°C 3.5 hours at 25°C 2 hours at 35°C 1.5 hours

Product for professional use. The purchaser undertakes to strictly follow the above warnings when applying the purchased product and the instructions in the safety data sheet.

FONDO PER PIASTRELLE A+B • Technical sheet • 05/11/2025

Sivit S.r.l.

Via Centallo 57, 10156, Torino, Italia | P.I. - C.F. 01012820013 | C.C.I.A.A. N. 478878 | Reg. Soc. Tribunale Torino N. 305/74

Sistema di gestione conforme alle ISO 9001:2015 – ISO 14001:2015 – ISO 45001:2018

commerciale@sivit.it | sivitsrl@pec.it | +39 011 273 00 33 | www.sivit.it

APPLICATION DATA AND TIMES

Dry to the touch (50% R.H.)	at 10°C 8-10 hours at 25°C 2 hours at 35°C 1.5hours
Coverage (50% R.H.)	at 23°C 12 to 36 hours
Environmental conditions of use	Temperatures between +15 °C and +30 °C and R.H. < 70% Minimum operating temperature: 5 °C

PERFORMANCE TECHNICAL DATA

Appearance	Satin
------------	-------

Product for professional use. The purchaser undertakes to strictly follow the above warnings when applying the purchased product and the instructions in the safety data sheet.

FONDO PER PIASTRELLE A+B • Technical sheet • 05/11/2025

Sivit S.r.l.

Via Centallo 57, 10156, Torino, Italia | P.I. - C.F. 01012820013 | C.C.I.A.A. N. 478878 | Reg. Soc. Tribunale Torino N. 305/74

Sistema di gestione conforme alle ISO 9001:2015 – ISO 14001:2015 – ISO 45001:2018

commerciale@sivit.it | sivit srl@pec.it | +39 011 273 00 33 | www.sivit.it