

# WALL PAINT PITTURA ANTICONDENSA

## Anti-mold atermic mural hydropitting

Single-component product easy to use based on copolymers of acrylic esters in water dispersion. By evaporation of the water a continuous film is obtained which turns out to be:

- atermic, thanks to the presence of glass microspheres that strongly reduce the thermal conductivity (with consequent reduction of the formation of condensation)
- anti-mold, thanks to the presence of a broad-spectrum fungicides, which hinder the formation of mold

### Description

Easy-to-use single-component product based on copolymers of acrylic esters in water base. By evaporation of the water, a continuous film is obtained which is:

- non thermic, thanks to the presence of glass microspheres that strongly reduce thermal conductivity (with consequent reduction of condensation)
- anti-mold, thanks to the presence of a broad spectrum fungicides, which hinder the formation of mold

### Uses

Surface restoration in environments with high humidity and poor ventilation, such as: cellars, closets, kitchens, canteens, bathrooms, swimming pools and food industries.

It can be pigmented with water-based pastes for water-based paints, in order to obtain light colors.

### Preparation of the support

Very absorbent and prone to chalking walls should be consolidated with FIBROPROTEX PRIMER.

Cement-based substrates must be left to season properly. To adhere to ceramic and other non-absorbent surfaces, a second coat of FONDO PER PIASTRELLE must be applied.

To restore missing parts and smooth the surfaces, use COLORSIVIT RASANTE.

### Application

PITTURA ANTICONDENSA paint should be applied in 2 stages, diluting with water (about 5-10%).

Each wall must be clean, dry, free from dust and mold residues.

Consumption is approximately 0.10-0.20 l/m<sup>2</sup> for each shot, depending on the absorption of the substrate.



**Product for professional use, the buyer undertakes to follow the above warnings in the application of the purchased product and the instructions in the safety data sheet.**

### Technical specifications

#### PRODUCT DATA

Colour	White or on request (for minimum batches of 150 liters)
Specific gravity (at 25°C)	0,90 +/- 0,05 g/ml
Dry residue	12.000 +/- 2.000 mPascal (spindle 2, rpm 4)
Viscosity (at 25 °C)	61%
Flash point	None
Solvent for cleaning tools	Water
Hazard symbols on labels	None
Storage	12 months, store in a dry place at a temperature between 5°C and 30°C

Product for professional use. The purchaser undertakes to strictly follow the above warnings when applying the purchased product and the instructions in the safety data sheet.

## APPLICATION DATA AND TIMES

Dry to the touch (50% R.H.)	at 7°C 70-80 min at 25°C 40-50 min at 30°C 20-30 min
Coating (50% R.H.)	at 25°C 4 hours
Environmental conditions of use	Temperatures between + 2°C and + 35°C and R.H. <80%

Product for professional use. The purchaser undertakes to strictly follow the above warnings when applying the purchased product and the instructions in the safety data sheet.

